

A Fast and Accurate Block Compression Solution for Spatiotemporal Kernel Density Visualization



Yue Zhong
Shenzhen University
2310273008@email.szu.edu.cn

Dingming Wu
Shenzhen University
dingming@szu.edu.cn

Tsz Nam Chan
Shenzhen University
edisonchan@szu.edu.cn


Wei Tu
Ruisheng Wang
Shenzhen University
{tuwei,ruiswang}@szu.edu.cn

Leong Hou U
University of Macau
ryanlhu@um.edu.mo


Joshua Zhexue Huang Shenzhen University zx.huang@szu.edu.cn


Overview of Spatiotemporal Kernel Density Visualization (STKDV)











(c) 7th October 2011

(d) 26th June 2013

Detect time-dependent hotspots using the location data of San Francisco 311 calls.

Color each pixel-timestamp (\mathbf{q}, t_i) pair based on the spatiotemporal kernel density function $\mathcal{F}_{\hat{P}}(\mathbf{q}, t_i)$, where

$$\mathcal{F}_{\widehat{P}}(\mathbf{q}, t_i) = \frac{1}{n} \sum_{(\mathbf{p}, t_{\mathbf{p}}) \in \widehat{P}} K_{\text{space}}^{(b_{\sigma})}(\mathbf{q}, \mathbf{p}) \cdot K_{\text{time}}^{(b_{\tau})}(t_i, t_{\mathbf{p}})$$

Commonly used spatial kernel functions and temporal kernel functions.

Kernel	$K_{\mathrm{space}}(\mathbf{q},\mathbf{p})$	$K_{\text{time}}(t_i, t_{\mathbf{p}})$
Triangular	$\begin{cases} 1 - \frac{1}{b\sigma} \mathbf{q} - \mathbf{p} _2 & \text{if } \mathbf{q} - \mathbf{p} _2 \le b_{\sigma} \\ 0 & \text{otherwise} \end{cases}$	$\begin{cases} 1 - \frac{1}{b_{\tau}} t_i - t_{\mathbf{p}} & \text{if } t_i - t_{\mathbf{p}} \le b_{\tau} \\ 0 & \text{otherwise} \end{cases}$
Epanechnikov	$\begin{cases} \frac{3}{4} \cdot \left(1 - \frac{1}{b_{\sigma}^2} \mathbf{q} - \mathbf{p} _2^2\right) & \text{if } \mathbf{q} - \mathbf{p} _2 \le b_{\sigma} \\ 0 & \text{otherwise} \end{cases}$	$\begin{cases} \frac{3}{4} \cdot \left(1 - \frac{1}{b_{\tau}^2} (t_i - t_{\mathbf{p}})^2\right) & \text{if } t_i - t_{\mathbf{p}} \le b_{\tau} \\ 0 & \text{otherwise} \end{cases}$
Quartic	$\begin{cases} \frac{15}{16} \cdot \left(1 - \frac{1}{b_{\sigma}^2} \mathbf{q} - \mathbf{p} _2^2\right)^2 & \text{if } \mathbf{q} - \mathbf{p} _2 \le b_{\sigma} \\ 0 & \text{otherwise} \end{cases}$	$\begin{cases} \frac{15}{16} \cdot \left(1 - \frac{1}{b_{\tau}^2} (t_i - t_p)^2\right)^2 & \text{if } t_i - t_p \le b_{\tau} \\ 0 & \text{otherwise} \end{cases}$


STKDV is computationally expensive, which takes O(XYTn) time. Example:

- The resolution size $(X \times Y)$: 1280×960
- The number of timestamps (T): 32
- The total number of data points (n): 1.83 million
- The total cost is: 71.96 trillion operations ③

Overview of Existing Solution: SWS and PREFIX

SWS:

 $\mathcal{F}_{\widehat{P}}(\mathbf{q},t_i)$



Only those data points $(\mathbf{p}, t_{\mathbf{p}})$ in $W(t_i)$ can contribute to $\mathcal{F}_{\hat{P}}(\mathbf{q}, t_i)$.


 $W(t_i)$ Efficiently update from $S_{W(t_i)}^{(u)}(\mathbf{q})$ to $S_{W(t_{i+1})}^{(u)}(\mathbf{q})$.

O(XY(T+n)).

The time complexity of SWS is

 $= \sum_{(\mathbf{p}, t_{\mathbf{p}}) \in \hat{P}} w \cdot K_{\text{space}}^{(b_{\sigma})}(\mathbf{q}, \mathbf{p}) \cdot \left(1 - \frac{1}{b_{\tau}^{2}} dist(t_{i}, t_{\mathbf{p}})^{2}\right)$ $= w \left(1 - \frac{t_{i}^{2}}{b_{\tau}^{2}}\right) S_{W(t_{i})}^{(0)}(\mathbf{q}) + \frac{2wt_{i}}{b_{\tau}^{2}} S_{W(t_{i})}^{(1)}(\mathbf{q}) - \frac{w}{b_{\tau}^{2}} S_{W(t_{i})}^{(2)}(\mathbf{q})$ $\text{where } S_{W(t_{i})}^{(u)}(\mathbf{q}) = \sum_{(\mathbf{p}, t_{\mathbf{p}}) \in W(t_{i})} t_{\mathbf{p}}^{u} \cdot K_{\text{space}}^{(b_{\sigma})}(\mathbf{q}, \mathbf{p})$

PREFIX:




First maintain the prefix-matrix with respect to all X×Y pixels for each end point in the time axis.


Once they have all prefix-matrices, they then evaluate each $S_{W(t_i)}^{(u)}(\mathbf{q})$ based on the following equation and compute $\mathcal{F}_{\hat{P}}(\mathbf{q}, t_i)$ for all pixels \mathbf{q} .

$$S_{W(t_i)}^{(u)}(\mathbf{q}) = S_{P(t_i+b_{\tau})}^{(u)}(\mathbf{q}) - S_{P(t_i-b_{\tau})}^{(u)}(\mathbf{q})$$


The time complexity of PREFIX is O(XYT + Yn).

Core ideas of Our Solution (COMP)





Real data often contain spatiotemporally close points.



 $A_{\mathcal{S}}(\mathbf{q}, t_i) = \frac{1}{n} \sum_{\mathcal{B} \in \mathcal{S}} \mathbb{C}(\mathcal{B}) \cdot K_{\text{space}}(\mathbf{q}, \mathbf{p}_{\mathcal{B}}) \cdot K_{\text{time}}(t_i, t_{\mathbf{p}_{\mathcal{B}}})$

COMP reduces data by merging nearby spatiotemporal points into block centers with weights.


How to determine the block size of COMP to ensure that the following absolute error guarantee holds?


$$|A_{\mathcal{S}}(\mathbf{q},t_i) - \mathcal{F}_P(\mathbf{q},t_i)| \leq \epsilon$$


Theorem 1. Given a location dataset P and an absolute error ϵ , we can achieve the absolute error guarantee ϵ if ω_B and λ_B of each block B in S have the following settings.


- (1) $\omega_{\mathcal{B}} = \frac{\sqrt{2} \cdot \epsilon \cdot b_{\sigma}}{2}$ and $\lambda_{\mathcal{B}} = \epsilon \cdot b_{\tau}$ using the triangular spatial and temporal kernels.
- (2) $\omega_{\mathcal{B}} = \frac{4\sqrt{2}\cdot\epsilon \cdot b_{\sigma}}{9}$ and $\lambda_{\mathcal{B}} = \frac{8\cdot\epsilon \cdot b_{\tau}}{9}$ using the Epanechnikov spatial and temporal kernels.
- (3) $\omega_{\mathcal{B}} = \frac{16\sqrt{6}\cdot\epsilon\cdot b_{\sigma}}{75}$ and $\lambda_{\mathcal{B}} = \frac{32\sqrt{3}\cdot\epsilon\cdot b_{\tau}}{75}$ using the quartic spatial and temporal kernels.

Experimental Results












1000000
100000
100000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
100000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
10000
1



(b) New York



(c) Chicago



The number of blocks, varying the absolute error ϵ . Response time for computing STKDV, varying the spatial resolution.